









Optimum surface removal and surface quality by use of speed-consistent gear drive This ergonomic miniature grinder allows easy and

optimum access on hard-to-reach areas. The high

run-out accuracy of the collet assures a high durability, an optimum material removal, and a high surface quality during grinding or milling. This grinder operates with an extreme low vibration.

High repeatability by gear motor without vanes

The robust construction assures a high longevity of your tool - even when used in continued operations.

Oilfree operation without loss of power is possible

Best ergonomic shape:

- Housing grip
- Housing material
- Noise level
- Vibrations
- Handling

Top-Speed-Grinder


Grinding and milling with an actual speed of 100.000 rpm

- optimum surface removal and surface quality by use of speed-consistent gear drive
- high repeatability by gear motor withous vanes
- oilfree operation without loss of power is possible
- ergonomic

High speed midget grinders, especially when used with highgrade steel inserts at relative high speed, are used for grinding, for deburring and also when treating non-metallic materials.



SPECIFICATIONS - TOP-SPEED-GRINDER



Twist Valve	Typ Part No.		GDS 009-1000B	(
Rear Air Exhaust			3146441E		
Speed (no load)	min ⁻¹	(rpm)) 100 000		
Max. power output	W	(hp)	90	(0.09)	
Air consumption (no load)	m³/min	(cfm)	0,2	(7.06)	
I.D. of air inlet hose	mm	(in)	4	(.16)	
Max. Ø of grinding tip	mm	(in)	5	(.20)	
Max. Ø of grinding insert	mm	(in)	3	(.12)	
Weight of tool	kg	(lbs)	0,3	(.66)	
Length of supply/exhaust hose	m	(in)	2/0,4	(78.7x15.7)	
Dimensions Ø DxL	mm	(in)	Ø 31x158	(1.22x6.22)	

Standard Equipment:	Part Number
Collet Ø 3 mm	314406
Spanner 9 mm	800401
Ring spanner 7 mm	821845
Nozzle	801565

Optional Accessories:	Part Number
Collet Ø 1,0 mm	315087
Collet Ø 1,1 mm	310003
Collet Ø 1,2 mm	314921
Collet Ø 1,4 mm	315157
Collet Ø 1,6 mm	310033
Collet Ø 2,0 mm	314693
Collet Ø 2,35 mm (3/32")	314694
Collet Ø 2,5 mm	314956
Collet Ø 3,175 mm (1/8")	314407
Collet Ø 3,25 mm	314946
Grinding tip for steel- and cast iron-shaft Ø 3 mm	
Ø 4 mm, length 8 mm	804916
Ø 5 mm, length 10 mm	804917
Ø 5 mm	804975

	2 c min, longar c min		001010
	Ø 5 mm, length 10 mm		804977
Grinding insert for stee	l- and cast iron-shaft Ø 3	3 mm	
	Head-Ø mm	Length mm	
	2 (5/64")	6 (1/4")	803061
	3 (1/8")	12 (15/32")	803062
	3 (1/8")	12 (15/32")	803076
	2 (5/64")	6 (1/4")	803084
	3 (1/8")	12 (15/32")	803085
	3 (1/8")	3 (1/8")	803097
	3 (1/8")	12 (15/32")	803115
	3 (1/8")	12 (15/32")	803125
	3 (1/8")	8 (5/16")	803136
	3 (1/8")	12 (15/32")	803145
Grinding insert for all m	naterials-shaft Ø 3 mm		
800000000	3 mm, length 14 m	m	804989

804976



Ø 3 mm, length 6 mm

